



KIP-3210F



IP Dome Panoramic 2.0 Mega Pixel PoE

High Definition 1080 Pixels

H.265+ Angle Lens 210° 3M Pixels, IR up to 15 meters

SPECIFICATIONS

Image Sensor	IMX307
Image Resolution	2 MP 1080P
Effective Pixels	1920*1080
Compression	H.265+/H.264
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB (0.001Lux@F1.2)
Scanning System	Progressive Scan
Length Lens	1.8mm
The Angle Lens	210°
Pixels Lens	Star level 3 MP Pixels
Min Illumination	0.001 Lux
Infrared LED	21μ x 3PCS
Infrared Distance	15M
IR Power On	CDS Auto Control
Day/Night	Color/ B&W (IR-CUT)
ONVIF	Support ONVIF 2.4
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
WDR, BLC, Motion Detection	Yes
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/VMS/Web
Housing	Metal ,IP66
IR Cut Filter	Yes
Operation Temperature	-40°C ~ +60°C RH95% Max
Storage Temperature	-30°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA PoE (802.3af, 36V to 57V) Support IEEE 802.3af
Dimension	Size : Φ 94 x 69(H) mm
Weight	650g