

DVR-8808

8CH Full 960H/D1 H.264 DVR

USB Mouse Control with GUI Display



FEATURES

USB Mouse Control with GUI OSD

- ❖ The GUI OSD interface is provided and used with your USB mouse.

Remote Surveillance with Browsers and CMS

- ❖ For web browsers, compatible with Internet Explorer, Mozilla Firefox, Google Chrome, Safari & Opera.
- ❖ For CMS software, available with our self-developed and free software, "General_CMS".

High Performance Design

- ❖ Definable "Resolution" / "Quality" / "IPS" by channels at your preferences to increase the recording efficiency, and avoid any important scenes to be missed.

Video Output

- ❖ Supports video output for both composite & VGA simultaneously.
- ❖ Support VGA resolution output up to 1920 x 1080.
- ❖ Support HDMI resolution output up to 1920 x 1080.

Intelligent Motion Recording

- ❖ Only the channel with an event will be recorded to effectively save a significant amount of hard disk space and have the maximized recording time.
- ❖ Supports pre-alarm recording(before 10 sec).

Dual-stream Design

- ❖ Main stream for local recording effects, extra stream for network remote view effects. Dual-stream parameters can be set separately, independently of each other.

PTZ Protocol

- ❖ Support more than 20 kinds protocol of the PTZ control

Remote Independent Operation

- ❖ Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

Multiplex

- ❖ Allows live display, record, playback, backup and network operation at the same time.

Backup Function

- ❖ USB 2.0 flash drive, USB mobile HDD, Network and USB DVD-RW.

Audio / Video Support

- ❖ 8 audio-in, 1 audio-out to record sounds.
- ❖ VGA interface built-in.
- ❖ HDMI interface built-in.

REAR PANEL



SPECIFICATIONS

Video System		NTSC / PAL (manual setting)	
Video Compression Format		H.264	
Video Input		8 channels (Composite video signal 1 Vp-p 75Ω BNC)	
Video Output (BNC)		Main Monitor Output (Composite video signal 1 Vp-p 75Ω BNC)	
Video Output (VGA)		Built-in (Output resolution up to 1920 x 1080)	
Video Output (HDMI)		Built-in (Output resolution up to 1920 x 1080)	
Audio Input / Output		8 audio input, 1 audio output (RCA)	
Maximum Recording Rate	Frame	960×480 pixels with 120 FPS <NTSC> / 960×576 pixels with 96 FPS <PAL> 704×480 pixels with 240 I FPS <NTSC> / 704×576 pixels with 200 FPS <PAL>	
	Field	704×240 pixels with 240 FPS <NTSC> / 704×288 pixels with 200 FPS <PAL>	
	CIF	352×240 pixels with 240 FPS <NTSC> / 352×288 pixels with 200 FPS <PAL>	
Image Quality Setting		Highest / Higher / High / Low / Lower / Lowest	
Playback resolution		8 channels x 960H/D1	
Hard Disk Storage		Accommodates 1 SATA HDD (1 HDD capacity up to 2TB)	
Quick Search		Time / Motion / Alarm search mode	
SATA Interface		Built-in	
Recording Mode		Manual / Timer / Motion / Alarm / Remote	
Multiplex Operation		Live display / record / playback / backup / network operations	
USB Mouse Control		YES	
Motion Detection Area		16 × 12 grids per channel	
Motion Detection Sensitivity		6 adjustable parameters for accurate detection	
Pre-alarm Recording		YES	
Backup Device		USB 2.0 flash drive / USB mobile HDD / Network / USB DVD-RW	
Web Transmitting Compression Format		H.264	
Ethernet		10/100 Base-T. Supports remote control and live view via Ethernet	
Mobile Surveillance		YES (Including iPad, iPhone, BlackBerry, Windows Mobile, Symbian & Android)	
Remote Surveillance (Operating System: Windows 7 / Vista / XP)	CMS:	Our self-developed and free software, "General_CMS"	
	Web Browser:	Internet Explorer, Mozilla Firefox, Google Chrome, Safari & Opera	
	Network Live Audio	YES	
	Max. on-line user:	10	
Network Protocol		TCP/IP, PPPOE, DHCP and DDNS	
Remote Independent Operation		YES	
Remote Event Download & Playback		YES	
Event Notification		FTP / E-Mail	
R.E.T.R. (Remote Event Trigger Recording)		YES	
IR Remote Control		Remotely control DVR and PTZ cameras via IR transmitter (IR receiver built-in)	
Picture Zoom		1X digital zoom	
PTZ Control		YES (built-in RS-485 port)	
Alarm I/O		NO	
Multilingual OSD		YES, support 28 kinds language.	
Watermark		YES	
Support 3G, WIFI, GPRS		YES	
Key Lock (Password Protection)		YES	
User Level		Administrator & Operator	
Video Loss Detection		YES	
Video Adjustable		Hue / Saturation / Contrast / Brightness	
Date Display Format		YY/MM/DD, MM/DD/YY & DD/MM/YY	
Daylight Saving		YES	
Power Source (±10%)		DC 12V @ 2A	
Power Consumption (±10%)		<7W without HDD	
Operating Temperature		-10°C ~ 60°C	
Dimensions (mm) **		Dimension: 210(D)x250(W)x45(H)	
System Recovery		System auto recovery after power failure	

*The specifications are subject to change without notice.

** Dimensional tolerance: ±5mm