



CIR-500S mini

PRODUCT DESCRIPTION:

- 3.5" Super Mini Configuration,Vandalproof;
- Super high Resulotion,X128 WDR,ICR Switch;
- Pan 360° Tilt 180° (Auto-Flip), Max 360°/sec;
- Built-in 10*10X Zoom with invert image;
- 4 Pattern, 8 Swing, 8 Group, Power-off Protection;
- RS-485, PELCO-D/P Protocol;
- 128 Preset, OSD Menu;
- 4 Ch Alarm In,1 Ch Alarm Out(Optional);
- With shockproof and weathproof cover, built-in fan and heater



Specification

Camera	Image device	Sony 1/4" Interline Transfer CCD	
	Signal System	NTSC 2:1 Interleaved	PAL 2:1 Interleaved
	Max.Pixels	811(H)*508(V) 410K NTSC	795(H)*596(V) 470K PAL
	Effective Pixels	768(H) x 494(V) 380K NTSC	752(H) * 582(V) 440K PAL
	Scan Frequency	H: 15.625 KHz/V : 50.00 Hz	H:15.734 KHz/V:59.94 Hz
	H.Resolution	500TV Lines (Color),570TV Lines (B/W)	
	S/N Ratio	50 dB (AGC OFF)	
	Zoom	100x $\frac{1}{4}$ ~10x Optical zoom,10x Digital Zoom $\frac{1}{4}$ %	
	Focus Length	F1.8 f=3.8 to 38mm	
	Day&Night	Auto/Day/Night(IR Cut Filter)	
	Min Illumination	Color 0.7Lux/ 0.02Lux(B/W) 50 IRE	
	White Balance	Auto/Manual(Red&Blue Gain Adjustable)	
	AGC	Normal/High/Off	
	BLC	Low/Middle/High/Off	
	Flicker less(selectable)	On/Off $\frac{1}{4}$ ~1/100 $\frac{1}{4}$ %	On/Off $\frac{1}{4}$ ~1/120 $\frac{1}{4}$ %
	Focus	Auto/Manual/Semi-Auto	
	Shutter speed	X128 ~ 1/120000 sec	
	Iris	Auto/Manual	
	SSNR	Low/Middle/High/Off	
Pan/Tilt	Pan/Tilt Speed	Preset:360°/Sec,Tilt:0°~180°/Sec;Manual:0.05°~360°/Sec(Zoom Proportional)	
	Rotation Range	Pan :360° (Endless)Tilt: 180°(Auto-Flip On $\frac{1}{4}$ %,95° (Normal Off)	
	Preset	127 preset(title, camera image setup available)	
	Pattern	4 pattern(1200 command/pattern, Approx.5 Minutes for Each Group)	
	Swing	8 Swings	
	Group	8 Group(Max.20 action entries for Each Group)	
	Other Function	Image Auto-flip, Auto Parking, Power-up Action.etc	